


Flow transmitter

SID10ADB10OG/



- 1 LED display
 2 setting pushbutton
 3 Tightening torque 25 Nm



Product characteristics

Number of inputs and outputs	Number of analog outputs: 1
Process connection	M18 x 1,5 Internal thread

Application

Media	Liquids
Medium temperature [°C]	-25...80
Pressure rating [bar]	300
MAWP (for applications according to CRN) [bar]	208

Liquids

Medium temperature [°C]	-25...80
-------------------------	----------

Electrical data

Operating voltage [V]	19...36 DC
Current consumption [mA]	< 60
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	10

Inputs / outputs

Number of inputs and outputs	Number of analog outputs: 1
------------------------------	-----------------------------



Flow transmitter

SID10ADB10OG/

Outputs		
Total number of outputs		1
Output signal		analog signal
Number of analog outputs		1
Analog current output [mA]		4...20
Max. load [Ω]		500
Overload protection		yes
Measuring/setting range		
Probe length L [mm]		45
Liquids		
Setting range [cm/s]		3...300
Greatest sensitivity [cm/s]		3...100
Accuracy / deviations		
Repeatability [cm/s]		1...5
Note on repeatability		for water 5...100 cm/s; 25 °C
		Factory setting
Temperature drift [cm/s x 1/K]		0.1; (for water 5...100 cm/s; 10...70 °C)
Measuring error [% of the final value]		$\pm 2... \pm 10$
Reaction times		
Response time [s]		1...10
Liquids		
Response time [s]		1...10
Operating conditions		
Ambient temperature [°C]		-25...80
Storage temperature [°C]		-25...100
Protection		IP 67
Tests / approvals		
EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	50 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	20 g (55...2000 Hz)
MTTF [years]		259
Mechanical data		
Weight [g]		230
Dimensions [mm]		M18 x 1.5
Thread designation		M18 x 1.5
Material		stainless steel (1.4404 / 316L); stainless steel (1.4301 / 304); PC; PBT-GF20; EPDM/X
Materials (wetted parts)		stainless steel (1.4404 / 316L); O-ring: FKM 80 Shore A
Process connection		M18 x 1,5 Internal thread
Displays / operating elements		
Display	Function	10 x LED, three-color

SI5004



Flow transmitter


SID10ADB10OG/

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A



Connection

